



# Vision

## EasyCombo

### B L U E T E C

Comprehensive  
vending solutions

30% more capacity than a standard machine. Features a refrigerated cabinet with different temperature areas offering an innovative way of selling FMCG products in just one machine, it features modular construction and are **adaptable to virtually any product and packaging** because all the channels are adaptable thanks to the innovative Jofemar design.

#### FEATURES

- Temperature under 5°C.
- Capacity for 6 and 2 height-adjustable trays with up to 10 channels each.
- FIFO (First In First Out) System. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting system with on/off programming.
- 1100 x 515 mm glass front door.
- Continuous performance self-testing.
- Health timer to prevent selling out-of-date products. Programmable expiration date by selection or channel.
- Flexible setup, and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 650 watts.

#### STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- High-capacity cash box with lock and optional auto-locking during extraction.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

#### CREDIT MANAGEMENT

- MDB or Executive protocol.
- Innovative Jofemar coin mechanism with five return tubes for up to five different coin values and the most reliable fraud-prevention systems.
- Allows installation of card and banknote readers.

#### PROGRAMMING

- General on site programming with the machine's keyboard and the LCD screen messages.
- Compatible with the Jofemar EasyFlash tooling for stock control and accounting
- Compatible with the latest telemetry systems for the end-to-end remote machine management.
- RS232 port with accounting data output.

#### OPTIONS

- Jofemar banknote reader.
- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Vandal-proof coin entry.
- Modem installation and Vending Track communication interface.
- Online operation with real-time control of users and sales.
- Management of up to two slave vending machine for higher capacity and number of selections.
- External microwave ovens detached column controlled by the master machine. Its availability and heating times depend on the selections. Self-activated when a product has been dispensed from the master machine. Individually heating time programmed per selection.

|                  | EASYCOMBO  |
|------------------|--|
| Temperature      | Under 5°C  |
| Maximum capacity | 6 trays of up to 10 channels and 2 trays of up to 7 channels |
| Elevator         | No   |
| Size (mm)        | 1,830 x 803 x 970  |
| Weight           | 297 kg   |
| Energy supply    | 230 V, 50 Hz*  |
| Cooling unit     | CFC-free R-134a  |

\*Check for other voltages.



VANDAL-PROOF  
LOCK



OPTIMISED  
CAPACITY AND  
VOLUME



ENERGY-SAVING  
LED LIGHTING



BANKNOTE AND  
COIN MECHANISM  
PAYMENT SYSTEMS



EASYFLEX  
DELIVERY SYSTEM



HEALTH TIMER:  
EXPIRATION  
PROGRAMMING BY  
TEMPERATURE



PRODUCT DELIVERY  
DETECTION  
PHOTOCELLS



EXPIRATION  
PROGRAMMING



Ctra. Marcilla km 2  
31350 PERALTA. Navarra SPAIN  
Tel. +34 948 75 12 12  
Fax +34 948 75 04 20

[www.jofemarmvending.com](http://www.jofemarmvending.com)

